

PM2118

AC/DC Digital Clamp Meter



SPECIFICATIONS	RANGE	ACCURACY
DCV	600V	±(0.5%+3)
ACV(40~65Hz)	0.01~600V	±(0.8%+5)
Ω	0~60MΩ	±(0.8%+3)
Continuity	<30Ω	<30Ω
ACA(40~65Hz)	200mA~400A	±(2.5%+5)
	400A~600A	±(3%+5)
DCA	10mA~400A	±(3%+3)
	400A~600A	±(3.5%+3)
Capacitance	0.1uF~6000uF	±(3%+3)
Frequency	40Hz-1000Hz	
LowZ	1.0~600V	±(0.8%+3)
DCuA	0~200uA	±(0.8%+3)
	-40~1000°C	±(1%+2)
°C/°F	-40~1832°F	±(1%+2)

FEATURE	
Counts	6000
RANGE	Auto
ACA	60A/600A
DCA	60A/600A
DCV	6V/60V/600V
ACA	6V/60V/600V
Continuity	√
Ω	6kΩ/60kΩ/600kΩ/6MΩ/60MΩ
DCuA	√200uA
Frequency(Clamp)	1KHz
Frequency(Voltage)	1KHz
°C/°F	√
LPF(1kHz -3dB)	√
LowZ	√
Capacitance	600uF/6000uF
Data Hold	√
BackLight	√
NCV	√
Low Battery Indication	√
Auto Power Off	√
Dual Display	√

GENERAL	
Power Supply	2 x 1.5V AAA Battery
Weight	250g
Size	189x70x37mm
Jaw Size	ø 24mm
Safety Rating	EN61010-1, EN61010-2-032, EN61326, CAT.III 600V



DIGITAL CLAMP METERS

PM2118S

Smart AC/DC Digital Clamp Meter



SPECIFICATIONS	RANGE	ACCURACY
DCV	0.5~600.0V	±(0.5%+3)
ACV(40~65Hz)	1.0~600V	±(0.8%+5)
Ω	0~10MΩ	±(0.8%+3)
Continuity	<30Ω	<30Ω
ACA(40~65Hz)	200mA~400A	±(2.5%+5)
	400A~600A	±(3%+5)
DCA	300mA~600A	±(3%+10)
	Frequency	40Hz-1000Hz

FEATURE	
Counts	6000
RANGE	Auto
ACA	60A/600A
DCA	60A/600A
DCV	6V/60V/600V
ACA	6V/60V/600V
Continuity	√
Ω	6kΩ/60kΩ/600kΩ/6MΩ/10MΩ
V/Ω/A Auto Scan	√
Frequency(Clamp)	1KHz
Frequency(Voltage)	1KHz
Data Hold	√
BackLight	√
NCV	√
Low Battery Indication	√
Auto Power Off	√
Dual Display	√

GENERAL	
Power Supply	2 x 1.5V AAA Battery
Weight	250g
Size	189x70x37mm
Jaw Size	ø 24mm
Safety Rating	EN61010-1, EN61010-2-032, EN61326, CAT.III 600V



DIGITAL CLAMP METERS

AC Voltage Measurement	AC Voltage & AC Current Measurement	AC Voltage & DC Current Measurement	AC Current Measurement

