

Table with 4 columns: Feature, Value, Unit, and Description. Rows include Supplier's name or trade mark (ELICA), Model identifier (K05XXXI-025-002), Annual Energy Consumption - AEC hood (48.5 kWh/a), Energy Efficiency Class (A), Fluid Dynamic Efficiency - FDE hood (30.2 %), Fluid Dynamic Efficiency class (A), Light Efficiency - LE hood (52.1 lux/W), Lighting Efficiency Class (A), Grease Filtering Efficiency - GFE hood (65.1 %), Grease Filtering Efficiency class (D), Minimum Air Flow in normal use (250 m³/h), Maximum Air Flow in normal use (475 m³/h), Air Flow at intensive/boost setting (605 m³/h), A-weighted Sound Power Emission at minimum speed (47 dB(A) re 1pW), A-weighted Sound Power Emission at maximum speed (62 dB(A) re 1pW), A-weighted Sound Power Emission at intensive or boost speed (67 dB(A) re 1pW), Power consumption off mode - Po (NA W), and Power consumption in standby mode - Ps (0.49 W).

Additional Product Information compliant to commission regulation (EU) No 66/2014 and UK SI 2019 No. 539

Table with 4 columns: Feature, Symbol, Value, Unit, and Description. Rows include Time increase factor (0.9), Energy Efficiency Index (EEL hood 52.8), Measured air flow rate at best efficiency point (QBEP 350 m³/h), Measured air pressure at best efficiency point (PBEP 410 Pa), Maximum air flow (Qmax NA m³/h), Measured electric power input at best efficiency point (WBEP 132 W), and Nominal power of the lighting system (WL 7 W).

