

# PRODUCT DATASHEET

## HALOPIN SST 48 W 230 V G9

HALOPIN® SUPERSTAR | Halogen lamps with G9 base



---

### Areas of application

- Workplace lighting
- Lighting for reading

---

### Product benefits

- Brilliant accent lighting
- Incredibly small dimensions for revolutionary new luminaire designs
- Robust filament design thanks to innovative, unique bulb pinch technology
- Approved for use in open luminaires (to IEC 60598-1)
- Simple handling thanks to G9 plug-in base/holder system
- No transformer required
- UV filter
- Complies with IEC 60432-3 thanks to integrated fuse function

---

### Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index  $R_a$ : 100
- Base: G9


## TECHNICAL DATA

### Electrical data

Nominal wattage	50 W
Construction wattage	50.00 W
Nominal voltage	230 V
Claimed equiv. conventional lamp power	60 W

### Photometrical data

Luminous flux	740 lm
Luminous efficacy	14 lm/W
Light color (designation)	Warm White
Color temperature	2800 K
Color rendering index Ra	100
Light color	1028



### Light technical data

Starting time	0.0 s
---------------	-------

### Dimensions & Weight

Overall length	43.00 mm
Light center length (LCL)	24,0 mm
Diameter	14.00 mm
Product weight	3.19 g

### Lifespan

Lifespan	2000 h
Number of switching cycles	50000

### Additional product data

Base (standard designation)	G9
Mercury-free	Yes

Design / version	Tube
------------------	------

### Capabilities

Dimmable	Yes
Burning position	Any

### Certificates & Standards

Energy efficiency class	G
Energy consumption	50.00 kWh/1000h



### Country-specific categorizations

ILCOS	HSGST/C/UB-48-230-G9-24
Order reference	66748 ECO SST

### Energy labelling regulation data acc EU 2019/2015

Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G9
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	43.00 mm
Height	14.00 mm
Width	14.00 mm
Chromaticity coordinate x	0.452
Chromaticity coordinate y	0.409
Beam angle	SPHERE_360

### DOWNLOAD DATA

DOWNLOAD DATA	
	CAD data 3-dim
	CAD data 3-dim

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899195394	Blister 2	119 mm x 139 mm x 17 mm	12.00 g	0.28 dm <sup>3</sup>
4008321945198	Blister 1	140 mm x 18 mm x 120 mm	14.50 g	0.30 dm <sup>3</sup>
4052899195400	Shipping box 20	164 mm x 148 mm x 130 mm	218.00 g	3.16 dm <sup>3</sup>
4008321945204	Shipping box 10	164 mm x 130 mm x 148 mm	222.02 g	3.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.