Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 9290013257

Type of light source:

Liebt course con tures	F 4.4	directional:	
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	_
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the neares	00 h), rounded	2	Energy efficiency class	F		
Useful luminou indicating if it re in a sphere (36 cone (120º) or in (90º)	efers to the flux 50°), in a wide	150 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode p expressed in W	ower (P _{on}),	1,7	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked stand for CLS, expres rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	59	Spectral power	See image		
dimensions	Width	25	distribution in the	in last page		
without	Depth	25		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	15			
		Chromaticity coordinates (x and y)	0,458 0,410			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,48	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-' : not applicable;

(b)'_-' : not applicable;

