



CorePro Plastic LEDcandles & lusters



CorePro LEDcandle ND 5-40W E14 840 B35 FR

The CorePro LEDcandles and lusters are designed for retrofit replacement of incandescent lamps and are particularly attractive for chandeliers. They are compatible with fixtures with an E14 holder for candles and E14 or E27 holders for lusters and are available in multiple color temperatures. LED lamps deliver huge energy savings of up to 80% energy-saving compared with halogen lamps and provide excellent quality of light. By offering a lifetime of 15,000 hours it lowers maintenance costs. The CorePro LED candles and lusters are perfect for your basic lighting needs.

Product data

General information	·	
Cap-Base	E14 [E14]	
CE mark	Yes	
EU RoHS compliant	Yes	
Nominal Lifetime (Nom)	15000 h	
Switching Cycle	50000	
Tier	CorePro	
Light technical		
Color Code	840 [CCT of 4000K]	
Luminous Flux (Nom)	470 lm	
Color Designation	Cool White (CW)	
Correlated Color Temperature (Nom)	4000 K	
Luminous Efficacy (rated) (Nom)	94.00 lm/W	
Color Consistency	<6	
Color Rendering Index (Nom)	80	

LLMF At End Of Nominal Lifetime (Nom) 70 %			
Operating and electrical			
Input Frequency	50 to 60 Hz		
Power (Nom)	5 W		
Lamp Current (Nom)	44 mA		
Wattage Equivalent	40 W		
Starting Time (Nom)	0.5 s		
Warm Up Time to 60% Light (Nom)	0.5 s		
Power Factor (Nom)	0.51		
Voltage (Nom)	220-240 V		
Temperature			
T-Case Maximum (Nom)	81 °C		


Datasheet, 2022, December 5 data subject to change

CorePro Plastic LEDcandles & lusters

Controls and dimming	
Dimmable	No
Mechanical and housing	
Bulb Finish	Frosted
Bulb Shape	B35 [B 35mm]
Approval and application	
Energy Efficiency Class	F
Energy Consumption kWh/1000 h	5 kWh
EPREL Registration Number	453200

Product data		
Full product code	871951431254800	
Order product name	CorePro LEDcandle ND 5-40W E14 840 B35	
	FR	
EAN/UPC - Product	8719514312548	
Order code	929002968802	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	10	
Material Nr. (12NC)	929002968802	
Net Weight (Piece)	0.040 kg	


Dimensional drawing




CorePro LEDcandle ND 5-40W E14 840 B35 FR

Product	D	С
CorePro LEDcandle ND 5-40W E14 840 B35 FR	38 mm	114 mm

Photometric data




LEDcandle CorePro 5W B35 E14 840-GUL



LEDcandle CorePro 5W B35 E14 840 FR-POC


CorePro Plastic LEDcandles & lusters


Photometric data



LEDcandle CorePro B35 5W E14 827 FR-LDD

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.